

# Aluminum PWC Trailers



PWCV1250A

DWC2000A



## STANDARD FEATURES:

- Welded Frame Construction\*
- Torsion axle standard on WCA1250-39 model
- Galvanized spoke wheels
- Diamond deck tread plate fenders
- Submersible LED Lights\*
- Winch with Strap
- Heat Shrink Wire Connectors\*
- 2" Couper Standard
- Fully Carpeted Treated Lumber
- 2.5" x 2.5" tongue
- Tongue jack

*Better Built by Magic Tilt*



WCA1250-39  
2 units coupled

Coupling Unit



## OPTIONAL FEATURES:

- Torsion axles on 13" wheel versions
- Radial Tires on 13" t&w
- Spare t&w
- Spare Carrier
- Mag Wheels on 13" versions
- S/S Bearing Protectors

Item Number	Model	Net Capacity	Tire Size	Boat Length	Total Width	Total Length
FA9150	WCA1250-39	1250	12C	8'-12'	50"	13'11"
TA17100	Coupling Unit				102"	
FA9123	PWCV1250A	1250	12C	8'-12'	65.5"	13'11"
FA9125	PWCV1270A	1270	8C	8'-12'	65.5"	13'11"
FA9100	PWCV1500A	1500	13C	8'-12'	70"	13'11"
FA9200	DWC2000A	2000	13C	8'-12'	101"	17'9"
FA9250	DWC2500A	2500	10E	8'-12'	101"	17'9"

\*Not standard on WCA1250-39